

RESIDENTIAL PRODUCTS



AIR CONDITIONERS

TRUCOMFORT™ VARIABLE SPEED



XV20i 4TTVO

Up to 21.5 SEER2/13.5 EER2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4-wire connections, 2 wire optional
- WeatherGuard™ Top



XV18 4TTV8

Up to 18.0 SEER2/12.5 EER2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4-wire connections, 2 wire optional



2-STAGE



XL17i 4TTX7

Up to 17.2 SEER2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Swept fan blade
- 2-stage Climatuff® compressor
- WeatherGuard™ Top



XR16 4TTR6

Up to 16.2 SEER2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

SINGLE STAGE



XR15 4TTL5

Up to 16.0 SEER2†

- Side Discharge
- 2-4 ton
- Copper tube aluminum fin coil
- Climatuff™ compressor



XL15i 4TTX5

Up to 16.0 SEER2†

- 1.5 – 5 ton
- Spine Fin™ coil
- Swept fan blade
- Climatuff® compressor
- WeatherGuard™ Top



XR15 4TTR5

Up to 16.0 SEER2†

- COMMON FEATURES:
- 1.5 – 5 ton
 - Spine Fin™ coil
 - Climatuff® compressor

XR14 4TTR4

Up to 14.8 SEER2†

XR13 4TTR3

Up to 13.8 SEER2†

3 PHASE



XR17 4TTA7

Up to 18.0 SEER

- 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor



XR14 4TTA4

Up to 16.5 SEER†

XR13 4TTA3

Up to 14.5 SEER†

COMMON FEATURES:

- 3, 3.5, 4 & 5 ton
- Spine Fin™ coil



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

HEAT PUMPS

TRUCOMFORT™ VARIABLE SPEED



XV20i 4TWVO

UP TO 20.5 SEER2/12.7 EER2/9.0 HSPF2†

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4-wire connections, 2 wire optional
- WeatherGuard™ Top



XV19 4TWL9

Up to 19.0 SEER2/9.0 HSPF2

- Side Discharge
- 2, 3, 4 & 5 ton
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Copper tube aluminum fin coil
- Climatuff® Variable Speed inverter compressor
- ComfortLink™ II capability



XV18 4TWV8

Up to 18.0 SEER2/12.5 EER2/8.5 HSPF2

- 2, 3, 4 & 5 ton
- Woven Spine Fin™ coil
- Variable-speed fan motor
- Swept fan blade
- Compressor sound insulator
- Climatuff® Variable Speed inverter compressor
- Trane Link Connectivity
- Standard 4-wire connections, 2 wire optional



2-STAGE



XL17i 4TWX7

Up to 17.2 SEER2/8.1 HSPF2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- Swept fan blade
- 2-stage Climatuff® compressor
- WeatherGuard™ Top



XR16 4TWR6

Up to 16.2 SEER2/8.1 HSPF2†

- 2, 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor

SINGLE STAGE



XR15 4TWL5

Up to 16.0 SEER2/8.1 HSPF2

- Side Discharge
- 2-4 ton
- Copper tube aluminum fin coil



XL15i 4TWX5

Up to 16.0 SEER2/8.1 HSPF2†

- 1.5 – 5 ton
- Spine Fin™ coil
- Swept fan blade
- Climatuff® compressor
- Compressor sound insulator (select models)
- WeatherGuard™ Top

3 PHASE



XR17 4TWA7

Up to 17.5 SEER/9.6 HSPF

- 3, 4 & 5 ton
- Spine Fin™ coil
- 2-stage Climatuff® compressor



XR14 4TWA4

Up to 15.5 SEER/9.5 HSPF

- 3, 3.5, 4 & 5 ton
- Spine Fin™ Coil



XR15 4TWR5

Up to 16.0 SEER2/8.1 HSPF2†

- COMMON FEATURES:
- 1.5 – 5 ton
 - Spine Fin™ coil
 - Climatuff® compressor
 - Compressor sound insulator (select models)

XR14 4TWR4

Up to 14.8 SEER2/7.8 HSPF2†

† ENERGY STAR® qualified system ratings available for select models.

90%+ AFUE CONDENSING



XC95m TUHM / TDHM

COMMUNICATING
Up to 97.3% AFUE

- 60 – 120 MBU input
- ComfortLink™ II capability
- Fully modulating gas valve
- Three-wire connections
- Variable-speed communicating ECM blower motor
- Continuous Comfort-R™ mode
- Single or two pipe vent options
- Digital user interface for easy set up and diagnostics
- Silicon nitride igniter
- Variable-speed draft inducer
- Certified to 2% air leakage
- ENERGY STAR® qualified



S9V2-VS

97% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Variable speed draft inducer

S9V2

96% AFUE

- Variable-speed ECM blower motor
- Comfort-R™ mode
- Compatible with 1-stage, 2-stage, and variable speed* OD equipment
- Two-speed draft inducer

S9X2

Up to 96% AFUE

- Compatible with 2 stage OD equipment
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer

COMMON 2-STAGE S-SERIES FEATURES INCLUDED

- 40 – 120 MBU input
- Two-stage heat
- Single or two pipe vent options
- Fully insulated/gasketed
- Dry contact Humidifier and EAC terminals
- Silicon nitride igniter
- Standard 34" height
- Certified to 1% air leakage
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified



S9X1

Up to 96% AFUE

- 40 – 120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM motor
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Single or two pipe vent options
- IFC board with digital configuration, status, and fault codes
- ENERGY STAR® qualified
- Certified to 1% air leakage



L9X1†

95% AFUE

- 50, 70, & 100 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Ultra-Low NOx Certified
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only



S9B1

92.1% AFUE

- 40 – 120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower motor
- Single-speed draft inducer
- Silicon nitride igniter
- Single or two pipe vent options
- Stainless steel heat exchanger

80% AFUE NON-CONDENSING



XC80 TDDC / TUDC

COMMUNICATING

- 60 – 140 MBU input
- ComfortLink™ II
- Continuous Comfort-R™ mode
- Two-stage heat
- Three-wire connections
- Two-speed draft inducer
- Silicon nitride igniter
- Simplified Trane CleanEffects™ connections
- Variable-speed communicating ECM blower motor
- Digital user interface for easy set up and diagnostics
- Certified to 2% air leakage

XV80 TDD2V / TUD2V

- 60 – 140 MBU input
- Two-stage heat
- Variable-speed ECM blower motor
- Comfort-R™ mode
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated/gasketed
- Factory wired for humidifier and EAC
- Certified to 2% air leakage



S8V2-C

- 40 – 140 MBU input
- Trane Link Communicating Capability
- Can be connected in communicating or 24V non-communicating modes
- Two-stage heat
- High Efficiency, Variable Speed Constant Airflow blower motor
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with Trane CleanEffects™



S8X2

- 40 – 140 MBU input
- Two-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Two-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Aluminized steel heat exchanger
- Compatible with Trane CleanEffects™



S8X1

- 26 – 120 MBU input
- Single-stage heat
- High efficiency 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Fully insulated**/gasketed
- Humidifier & EAC terminals
- Certified to 1% air leakage



L8V1†

- 40 – 100 MBU input
- Single-stage heat
- Variable-speed blower motor
- Variable-speed draft inducer
- Ultra-Low NOx Certified
- Certified to 1% air leakage
- † California Only



L8X1†

- 55 – 100 MBU input
- Single-stage heat
- 5 tap Constant Torque ECM blower
- 14 ng/J operation
- Silicon nitride igniter
- Fully insulated cabinet
- † California Only



S8B1

- 26-120 MBU input
- Single-stage heat
- 9 tap Constant Torque ECM blower
- Single-speed draft inducer
- Silicon nitride igniter
- Certified to 1.4% air leakage

*Relay panel required when matched with variable speed outdoor units

**14.5" models do not contain blower compartment insulation



QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

COILS

CASED MULTI-POSITION



4TXC

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Enhanced fin design for efficiency and humidity control
- Double-sloped high temp drain pan
- All-Aluminum to prevent formicary corrosion



4MXC

- Single stage equipment only
- Fixed orifice
- TXV kit available for expanded ratings and applications (heat pump capable)
- All-aluminum to prevent formicary corrosion



4PXC-D / 4PXC-U

U = Upflow/Downflow*
D = Downflow only**

(Optimized for downflow efficiency and ratings)

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Double-sloped high temp drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion

UNCASED



4AXA

- TXV (heat pump capable)
- Single sloped non-corrosive drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion
- Single and 2-stage equipment only
- Shorter depth ideal for plenum placement



4PXA

- Single, 2-stage and variable speed equipment
- TXV (heat pump capable)
- Double-sloped high temp drain pan
- Enhanced fin design for efficiency and humidity control
- All-aluminum to prevent formicary corrosion

CASED



4PXF

- Single, 2-stage and variable speed equipment
- TXV (Heat pump capable)
- High temp drain pan
- Copper/Aluminum

Functional Parts



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

*Convertible to horizontal left or right with kit. **Convertible to horizontal right with kit.

AIR HANDLERS

HYPERION™ AIR HANDLERS



TAMX

- Trane Link compatible or 24V Operation
- 2 – 5 ton
- Continuous Comfort-R™ mode
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- Electronic expansion valve
- Variable-speed ECM blower motor
- Meets 2% air leakage requirements



TAM9

- ComfortLink™ II or 24V Operation
- 2 – 5 ton
- Continuous Comfort-R™ mode
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- Electronic expansion valve
- Variable-speed ECM blower motor
- Meets 2% air leakage requirements



GAM5

- 1.5 – 5 ton
- High efficiency four-speed ECM blower motor
- Composite Vortica™ blower housing
- All-aluminum coil
- Double wall modular cabinet
- Multi-position installation
- Side return option
- R-410A TXV
- Meets 2% air leakage requirements

CONVERTIBLE



TEM8

- ComfortLink™II or 24V Operation

COMMON FEATURES FOR TEM8 AND TEM6:

- 2 – 5 ton
- Variable-speed ECM blower motor
- All-aluminum coil
- R-410A TXV

TEM6

- 24V Operation

- Multi-position installation
- Metal Vortica™ blower
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements

TEM4

- 2 – 5 ton
- ECM blower motor
- Metal Vortica™ blower
- All-aluminum coil
- Galvanized steel metal cabinet
- R-410A TXV
- Multi-position installation
- Meets 2% air leakage requirements

Coil



Functional Parts

Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

UPFLOW



TMM5

- 2 – 3 ton
- Upflow design with front and bottom return options
- ECM blower motor
- R-410A TXV
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements
- All-aluminum coil

TMM4

- 1.5 – 3 ton
- Upflow design with front and bottom return options
- Fixed orifice
- Optional TXV kit
- Multi-speed PSC blower motor
- Galvanized steel metal cabinet
- Meets 2% air leakage requirements
- All-aluminum coil

P-SERIES MODULAR BLOWER



POV0†

- 34 Inch Cabinet Height
- High efficiency, variable speed blower motor.
- Fully insulated cabinet
- 4-way multi-poise
- Entirely electric operation
- † California Only

TRANE CLEANEFFECTS™



EFD

- Up to 100 times more effective than a standard 1" throwaway filter
- Power door provides easy access to internal components and features a filter status display as well as safety interlocks that automatically shut down the power when the door is opened for maintenance or cleaning
- Removes particles down to 0.3 micron in size
- Removes more than 99% of a surrogate for the virus that causes Covid-19 within 30 minutes
- ComfortLink II™ communicating or 24 volt capability
- Zero ozone emissions. Cleaner air without harmful ozone byproducts so you can breathe easier
- Allergy and Asthma Friendly® Certified
- Quiet operation



QUIKBOX



EQBFM

- MERV 11 and MERV 13 filter options
- Quick shirt box type design
- Stores flat, installs in seconds
- 7 sizes to match most cabinet widths
- Backward compatible for all Perfect Fit (TFM) filter boxes
- New smaller cabinet to meet competitive brands
- Low pressure drop; up to 6 mos. lifecycle

SLIMFIT FILTER



BAYSF 1165, 1185, 1235, 11255

- 1" Pleated Filter, MERV 4 rated, lasts up to 90 days
- Made-to-fit cabinet sizes for TEM Air Handlers and S9V and S9X furnace side return cabinets
- 2" depth low profile painted steel cabinet with hinged door for easy filter replacement

EVAPORATIVE HUMIDIFIERS



EHUMD500

FAN POWERED

- Capacity: 18 gallons per day
- Sq. Ft. Capacity: Up to 4,200
- Unit Type: Power humidifier/automatic control



EHUMD300

LARGE BYPASS

- Capacity: 16.8 gallons per day
- Sq. Ft. Capacity: Up to 4,000
- Unit Type: Large bypass humidifier/automatic control

EHUMD200

SMALL BYPASS

- Capacity: 12 gallons per day
- Sq. Ft. Capacity: Up to 3,000
- Unit Type: Small bypass humidifier/manual control



EHUMD800

- Capacity: 11 – 34.6 gallons per day
- Sq. Ft. Capacity: Up to 5,000

EHUMD800LC

- For 120V applications only
- For low conductivity water applications
- Up to 11 gal. per day output
- Replaceable LC canister available

DEHUMIDIFIER



EDHUM70H

WATER REMOVAL:
70 Pints/Day
8.75 Gallons /Day



EDHUM98

WATER REMOVAL:
98 Pints/Day
12.25 Gallons /Day



EDHUM120

WATER REMOVAL:
120 Pints/Day
15.125 Gallons /Day

COMMON FEATURES:

- Features a horizontal configuration with optional vertical discharge
- Designed for quiet operation
- Engineered for low temperature operation providing comfort year round
- Optional digital controller for outdoor air ventilation and humidity control
- Superior MERV-13 filtration to improve indoor air quality
- Ducting options for fresh outdoor air ventilation to meet ASHRAE 62.2 ventilation requirements
- Push button reset for transformer protection

VENTILATION



EERV100 EERV200 EERV300

COMMON FEATURES:

- Static plate energy transfer core for efficient transfer of heat and moisture
- MERV 8 replaceable filter included
- Multi position mounting
- Pull-down door latches for quick service access



EVENQF130V

- 62.2 Compliant Ventilation
- Full ECM Motor with Intelligent Logic Controller
- Adjustable airflow from 40 to 130 cfm to meet ventilation codes for all size homes
- 24V functionality from a smart thermostat, or use the on-board controller for "set-it and forget it" installation
- MERV 8 filter included for improved IAQ

Functional
Parts



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

SMART THERMOSTATS

CONNECTED CONTROLS



LINK360 UX360, SC360

SMART THERMOSTAT & SYSTEM CONTROLLER

- TruComfort™ Variable Speed
- Remote wired temperature sensor available through the hub
- Remote wireless indoor temperature and humidity sensor (optional): ZSENS930AW00MA
- Mobile app compatible with built-in
- Z-Wave bridge (download Trane Home mobile app)
- Trane Diagnostics
- Trane Diagnostics mobile app compatibility allows for easy technician commissioning and servicing
- WiFi connection
- Control from a smartphone, tablet, or computer
- 7" diagonal color touchscreen
- 1-Touch Presets - Home, Away, Sleep
- 7 Day programmable with up to four schedules per day
- Smart Continuous Fan
- Adjustable Continuous Airflow (35-100%)
- Five day weather forecast
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over-the-air Software Upgrade
- Color: Designer White



XL1050 TZON1050

- ComfortLink™ II communications
- ComfortLink™ II zoning
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
- Remote ID, OD sensor connections
- Remote Climate Access included
- Built in Bridge for Z-Wave devices
- Connect over 200 Z-Wave devices
- Trane Diagnostics ready
- WiFi (802.11 b/g/n) or Ethernet connection
- Control from a smartphone, tablet, or computer
- 7" diagonal color HD display
- 1-touch presets - Home, Away, Sleep
- 7-day programmable with up to four schedules per day
- Customizable home screen
- Runtime history
- Allergy and quick clean air cycles
- Smart continuous fan
- Adjustable continuous airflow
- Ventilation control*
- Service, filter, humidifier, UV light, air cleaner reminders
- 5-day weather forecast, weather radar, and alerts
- Indoor relative humidity display
- Test modes and alert diagnostics
- Over the air or local software upgrade
- BK Terminal for humidity control
- Color: Designer Silver



XL1040 TZON1040

ZONING COMMUNICATING SENSOR WITH DISPLAY

- For use with ComfortLink™ II Zoning Systems
- 3-Wire Communicating Zone Sensor
- 4.3" diagonal color touchscreen
- Zone Mode - Auto only
- Fan Mode - Auto/On
- Displays Zone Temperature & Relative Humidity.
- Average multiple zone temp sensors
- Displays Outdoor Temperature (Trane Home™ registration or wired ODT required)
- Clean Screen Function
- 3 Levels of Restricted Access
- Fahrenheit or Celsius
- Adjust zone Setpoint at 1040, 1050, and from the Trane Home™ app
- Schedule 1040, 1050 from the Trane Home app
- Zone Schedule Override - Permanent Hold
- Enter zone name at 1040 and 1050
- Local software upgrades
- Screen color with backlit options
- Screen saver options



XL850 TCONT850

- Remote Climate Access included**
- Built in Bridge for Z-Wave devices
- ComfortLink™ II communications
- Wi-Fi or Ethernet Connectivity
- Trane Diagnostics ready
- Compatible with 24 volt systems*
 - 5 heat / 2 cool
- 7-day programmable with up to 4 periods/day
- 4.3" color display
- Dual Fuel Capable
- 2 filter change reminders
- 5-day weather forecast, local radar & alerts
- Allergy and quick clean cycles
- Ventilation control*
- Maintenance reminders
- Customizable home screen
- Embedded diagnostics
- Color: Designer Silver

XL824 TCONT824

- ENERGY STAR® certified
- Remote Climate Access included**
- Wi-Fi or Ethernet connectivity
- Built in Bridge for Z-Wave devices
- Trane Diagnostics ready
- Used with conventional 24 volt systems
- 5 heat / 2 cool
- 7-day programmable
- 4.3" color display
- 2 aux dry contacts***
- Humidity sensor
- Humidifier, ventilation, and dehumidifier control
- 2 filter change reminders
- 5-day weather forecast, local radar & alerts
- Dual Fuel capable
- Allergy and quick clean cycles
- Maintenance reminders
- Customizable home screen
- Embedded diagnostics
- Smart continuous fan
- Color: Designer Silver



XR724 TCONT724

- Remote Climate Access included**
- Wi-Fi Connectivity
- 4 heat/2 cool
- Z-Wave Connectivity****
- Trane Diagnostics ready
- 4.3" diagonal LCD touchscreen
- Screen lock out and guest lock out
- Built-in humidity sensor
- Dehumidification setting
- Dual Fuel capable
- Filter, maintenance and humidifier service reminder alerts
- Color: Silver



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

SENSORS



ZZSENSAL0400

WIRED INDOOR TEMPERATURE SENSOR

- Indoor sensor for use with TZON1050 TCONT402A TCONT624 TCONT824 TCONT850

BAYSENS01

WIRED OUTDOOR TEMPERATURE SENSOR

- Outdoor sensor for use with TZON1050 TCONT401A TCONT402A TCONT624 TCONT824 TCONT850



ZSENS930

INDOOR WIRELESS TEMPERATURE AND HUMIDITY SENSOR

- Z-Wave device
- Monitor through Trane® Home mobile app
- Integrates with built-in Bridge of TZON1050 TCONT824 TCONT850



*BAY24VRPAC52DC Relay Panel required.

**Complimentary service for up to 8 professionally installed smart thermostats. Complimentary service includes up to 1 lighting or appliance module per control (maximum 8) installed. Unlimited Trane® Home Wi-Fi cameras (live streaming only) is included with complimentary Trane® Home remote climate access. Cameras and lighting controls are optional purchase.

***Auxiliary dry contacts may be configured to control 1) whole house humidifier; 2) dehumidifier; 3) ventilation system.

****Requires Z-Wave Bridge, purchase separately to connect to Trane Home Mobile App.

TRADITIONAL THERMOSTATS

7-DAY OR 5/1/1 PROGRAMMABLE



XR303 TCONT303

- 4 heat/2 cool
- Humidity sensor
- Dual fuel capable

COMMON FEATURES

- 5" Interactive touch screen
- Auto changeover
- Real-time clock

XR302 TCONT302

- 4 heat/2 cool
- Dual fuel capable

- Large back lit display
- Armchair programming
- Air filter reminder



XR203 TCONT203

- 4 heat/2 cool
- Dual fuel capable

COMMON FEATURES

- 3.5" Diagonal Backlit Display
- Simple programming
- Standard wiring terminal block



XR202 TCONT202

- 1 heat/1 cool

- Simultaneous display
- Soft key controls

NON-PROGRAMMABLE



XR103 TCONT103

- 2 heat/1 cool HP only
- Configurable Switchover Valve
- Emergency Heat
- Common required

COMMON FEATURES

- Push Button, Non-Programmable
- 1.9" Diagonal Display
- Fahrenheit or Celsius



XR102 TCONT102

- Up to 1 heat/1 cool
- No Common Terminal
- Battery Powered Only

SENSORS



ZZSENSALO300

WIRED INDOOR TEMPERATURE SENSOR

- Indoor sensor for use with TCONT303 TCONT302

BAYSEN30ATEMPA

WIRED OUTDOOR TEMPERATURE SENSOR

- Outdoor sensor for use with TCONT303 TCONT302

Functional Parts



Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at Trane.com or by phone at 855-260-2975, otherwise Trane's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ComfortSite.com.

QUESTIONS ABOUT WARRANTY?
CONTACT YOUR LOCAL TRANE REPRESENTATIVE.

PACKAGED

COOLING



XR13.4c 4TCC4

13.40 SEER2

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase Only (208v/230v)
- Climatuff® Compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- Microchannel evaporator coil on 2, 2.5, 3, 3.5 and 4 ton units
- CleanEffects™ Compatible (horizontal only)



EARTHWISE™ HYBRID DUAL FUEL



XL15c 4DCZ5

Up to 15.00 SEER2/7.20 HSPF2

- 2, 3, 4 and 5 ton
- 1-Phase Only (208v/230v)
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Spine Fin™ condenser
- Comfort-R™ mode
- Composite Vortica™ blower
- Heat pump and/or 2-stage gas heat operation
- All stainless steel heating system
- Ultra quiet
- CleanEffects™ Compatible (horizontal only)



XL16c 4WCZ6

Up to 16.00 SEER/8.20 HSPF

- 3, 4, and 5 ton
- 3-Phase Only (208v/230v & 460v)
- 2-stage Climatuff® compressor
- Variable-speed indoor blower motor
- Comfort-R™ mode
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- CleanEffects™ Compatible (horizontal only)



XR13.4c 4WCC4

13.40 SEER2/7.00 HSPF2

- 2, 2.5, 3, 3.5, 4 and 5 ton
- 1-Phase Only (208v/230v)
- Climatuff® Compressor
- Spine Fin™ condenser
- Tough corrosion and UV resistant paint
- Composite Vortica™ blower
- Demand defrost
- CleanEffects™ Compatible (horizontal only)



XL15c 4WCZ5

Up to 15.00 SEER2/7.50 HSPF2

- 2, 3, 4, and 5 ton
- 1-Phase Only (208v/230v)
- Climatuff® compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- CleanEffects™ Compatible (horizontal only)



XL14c 4WCY4

14.25 SEER/8.00 HSPF

- 3, 4 and 5 ton
- 3-Phase Only (208v/230v)
- Climatuff® compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Tough corrosion and UV resistant paint
- Demand defrost
- Ultra quiet
- CleanEffects™ Compatible (horizontal only)



XR14h 4WHC4

OVER/UNDER
13.40 SEER2/6.70 HSPF2

- 2, 2.5, 3, 3.5 ton
- 1-Phase Only (208v/230v)
- DuraTuff™ outdoor plate fin coil
- Direct drive two-speed blower motor



GAS/ELECTRIC



XL16c 4YCZ6

Up to 16.60 SEER/80% AFUE

- 3, 4, and 5 ton
- 3-Phase Only (208v/230v & 460v)
- 2-stage Climatuff® compressor
- 2-stage gas heat
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Tough corrosion and UV-resistant paint
- All stainless steel heating system
- Ultra quiet
- CleanEffects™ Compatible (horizontal only)



XL15c 4YCZ5

Up to 15.00 SEER2/81% AFUE

- 2, 3, 4, and 5 ton
- 1-Phase Only (208v/230v)
- 2-stage gas heat
- Climatuff® compressor
- Variable-speed indoor blower motor
- Composite Vortica™ blower
- Comfort-R™ mode
- Spine Fin™ condenser
- Ultra quiet
- Tough corrosion and UV resistant paint
- All stainless steel heating system
- CleanEffects™ Compatible (horizontal only)



XL14c 4YCZ4

14.30 SEER/80% AFUE

- 3, 4 and 5 ton
- 3-Phase Only (208v/230v)
- Climatuff® compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV-resistant paint
- CleanEffects™ Compatible (horizontal only)



XR13.4c 4YCC4

13.40 SEER2/81% AFUE

- 2, 2.5, 3, 3.5, 4 and 5 Ton
- 1-Phase Only (208v/230v)
- Climatuff® Compressor
- Spine Fin™ condenser
- Composite Vortica™ blower
- All stainless steel heating system
- Tough corrosion and UV resistant paint
- CleanEffects™ Compatible (horizontal only)



Compressor Coil Functional Parts

Heat Exchanger Compressor Coil Functional Parts

All Trane Packaged systems have a Base Limited Warranty of 5 years on the compressor, coil, and functional parts. Gas/Electric and Earthwise Hybrid Dual Fuel systems have a Base Limited Warranty of 20 years on the heat exchanger.

Limited Warranty Term for Trane Products Installed in Commercial Applications:
Coil, Parts – 1 year Limited Warranty; Compressor – 5 years Limited Warranty;
Packaged Unit Heat Exchanger – 5 years

QUESTIONS ABOUT WARRANTY? CONTACT YOUR LOCAL TRANE REPRESENTATIVE.